



[File # 019467_0_000](#)
(Class 4228-81)



[File # E10822](#)

Tiger-Vac is pleased to announce its new line of Regenerative Blowers with Premium Efficiency Explosion Proof Motors. These Motors are manufactured by Baldor®, a widely recognized company with many years of supplying high quality, high performance Explosion Proof Motors. The Regenerative Blowers are supplied by Tiger-Vac. With over 40 years of experience in the Explosion Proof Vacuum Cleaner industry our Blowers, combined with Baldor® Motors create a Motor/Blower combination suitable to be used in hazardous location. Baldor® Motors are certified by CSA and UL. both Tiger-Vac and Baldor® are ISO 9001:2008 certified.

- Manufactured in the USA - ISO 9001:2008 compliant
- UL/CSA compliant - Declarations of conformity on file
- Maximum Flow: 285 CFM
- Maximum Vacuum: >170" H₂O
- Standard Motor: 7.5 HP, TEFC
- Cast aluminum Blower Housing, Impeller and Cover
- Cast aluminum Threaded Flanges. 2.5" F-NPT
- UL and CSA approved motor with permanently sealed ball bearings
- Inlet and Outlet internal muffling
- Quiet operation. dB(A) within OSHA standards
- For industrial applications
- Available with the ability to stand up to corrosive chemical processing. Baldor® Motors come standard already coated with a corrosion resistant epoxy finish. Tiger-Vac Regenerative Blowers can also be coated with an epoxy finish upon request.

Specifications

Part Number	Horse Power	Blower Stage(s)	Maximum Airflow	Maximum Vacuum	Recommended VRV setting	Voltage @ 60Hz	Phase	Recommended Amp Setting for Overload
212762A	7.5 HP	1	285 CFM	>170" H ₂ O	95" H ₂ O	230/460V	3	18/9A
212762AE	7.5 HP	1	285 CFM	>170" H ₂ O	95" H ₂ O	230/460V	3	18/9A
212762B	7.5 HP	1	285 CFM	>170" H ₂ O	95" H ₂ O	575V	3	N/A
212762BE	7.5 HP	1	285 CFM	>170" H ₂ O	95" H ₂ O	575V	3	N/A

Part Number	Inlet & Outlet F-NPT Thread	Baldor Premium Efficiency Explosion Proof Motor Cat.#	XP Motor Class - Group	RPM	Nema	Weight (Motor + Blower)	Dimensions (Horizontal Mounting)	Capable of Vertical Mounting
Continued on next page...								

Specifications Continued...

Part Number	Inlet & Outlet F-NPT Thread	Baldor Premium Efficiency Explosion Proof Motor Cat.#	XP Motor Class - Group	RPM	Nema	Weight (Motor + Blower)	Dimensions (Horizontal Mounting)	Capable of Vertical Mounting
212762A	2.5"	VEM7045T	I - D, II - F & G	3500	213TC	242 Lbs	H20"xW19"xL27"	No
212762AE	2.5"	VEM7045T-E	I - D, II - E, F & G	3500	213TC	N/A	N/A	No
212762B	2.5"	VEM7045T-5	I - D, II - F & G	3500	213TC	N/A	N/A	No
212762BE	2.5"	VEM7045T-E-5	I - D, II - E, F & G	3500	213TC	N/A	N/A	No

